
# Metrotile® Qube Prestige ACO




## Design



Overall Length	1305 mm
Length of Cover	1260 mm
Overall Width	350 mm
Width of Cover	321 mm
Minimum pitch	15° (27 %)
Maximum pitch	90°
Roof Cover	0.405 m <sup>2</sup>
Tiles per m <sup>2</sup>	2.47
Weight/panel	2.60 kg
Weight/area	6.42 kg/m <sup>2</sup>

### Material structure



- 1 Super durable powder coating (> 80 µm)
- 2 Polyurethane primer
- 3 Zinc-aluminium-magnesium alloy
- 4 Steel 0.50 mm
- 5 Zinc-aluminium-magnesium alloy
- 6 Polyester primer
- 7 Sound absorbing pads

## **Steel specification**

The Metrotile Qube Prestige ACO tile is made from pre primed zinc-aluminium-magnesium coated steel that when combined with the extra durable powder coating finish provides optimal performance. The grade of steel used is designed to allow pressing without cracking while at the same time is ridged enough to tolerate reasonable loads.

Steel Thickness	0.50 mm
Steel Grade	DX53D
Zinc-aluminium-magnesium Coating Mass	250 g/m <sup>2</sup>
Zinc-aluminium-magnesium Coating Grade	ZM250

## Coating specification

**Polyester Powder Coating:** The finish coating is an extremly durable Polyester Powder Coating that is applied post pressing.

**Polyurethane primer:** The primer is applied by a coil coating process, this coating provides increased corrosion protection and a surface for superior adhesion of the Powder Coating that is applied.

**Polyester Backer Coating:** This coating provides increased durability to the underside of the tiles.

#### **Colours**











High-gloss black

High-gloss bordeaux red