



Design



Overall Length*	1165 mm [± 3 mm]
Length of Cover*	1085 mm
Overall Width*	400 mm [± 3 mm]
Width of Cover	368 mm
Minimum pitch	15° (27 %)
Maximum pitch	90°
Up stand	25 mm
Down turn	25 mm
Roof Cover*	0.40 m ²
Tiles per m ²	2.5
Weight/panel	3.00 kg
Weight/area	7.5 kg/m ²
Batten space	368 mm

* The measurements and the weight may vary slightly by the finish that is added to the accessory.

Material structure



- 1 Transparent protection layer
- 2 Stone granules
- 3 Coloured acrylic basecoat
- 4 Polyurethane primer
- 5 Zinc-aluminium-magnesium alloy
- 6 Steel
- 7 Zinc-aluminium-magnesium alloy
- 8 Polyester backer coating

Steel specification

The Metrotile Romana tile is made of ZM250. ZM250 is a steel that is coated with alloy of 93,5 % zinc, 3,5 % aluminium and 3 % magnesium. The grade of steel used is designed to allow pressing without cracking while at the same time is ridged enough to tolerate reasonable loads.

Steel Thickness	0.50 mm
Steel Grade	DX53D
Zinc-aluminium-magnesium Coating Mass	250 g/m ²
Zinc-aluminium-magnesium Coating Grade	ZM250

Textured surface

Stone chip granules are applied to provide an attractive textured finish which at the same time enhance resistance to UV radiation. Granules are ceramic coated with lightfast heat resistant pigments.

Coating specification

Transparent protection layer: Clear 100% acrylic resin coating for granule binding and a semi-gloss finish. It helps enhance the appearance as well as increase the resistance to physical damage.

Stone Chip: Carefully selected granules provide excellent surface coverage and attractive natural looking and lasting colours.

Basecoat: A tough opaque coating based on acrylic resin. It bonds the stone chips and protects the underlying layer from water and UV radiation. It has good UV resistance and retains its flexibility although it does become harder after the first few weeks.

Polyurethane primer: The primer is applied by a coil coating process, this coating provides increased corrosion protection and a surface for superior adhesion of the basecoat that is applied.

Polyester Backer Coating: This coating provides increased durability to the underside of the tiles.

Colours



Terracotta

Tuscany

Coffee

Scarlet

Coal Black

Ironbark

Zebra Intense

Victorian Red