Metrotile[®] Shingle




Design



Overall Length*	1335 mm [± 3 mm]
Length of Cover*	1240 mm
Overall Width*	290 mm [± 3 mm]
Width of Cover	252 mm
Minimum pitch	15° (27 %)
Maximum pitch	90°
Roof Cover*	0.311 m ²
Tiles per m ²	3.21
Weight/panel	2.00 kg
Weight/area	6.43 kg/m ²

* The measurements and the weight may vary slightly by the finish that is added to the accessory.

Material structure



Steel specification

The Metrotile Shingle tile is made of Aluminium Zinc alloy coated steel. The grade of steel used is designed to allow forming without cracking or significant elastic recovery and at the same time to be rigid enough to tolerate reasonable loads without excessive deformation.

Steel Thickness	0.41 mm
Steel Grade	DX52D
Aluzinc [®] Coating Mass	150 g/m²
Aluzinc [®] Coating Grade	AZ150

Coating specification

Overglaze: Clear 100% acrylic resin coating for granule binding and a semi-gloss finish. It helps enhance the appearance as well as increase the resistance to physical damage.

Stone Chip: Carefully selected granules provide excellent surface coverage and attractive natural looking and lasting colours.


Basecoat: A tough opaque coating based on acrylic resin. It bonds the stone chips and protects the underlying layer from water and UV radiation. It has good UV resistance and retains its flexibility although it does become harder after the first few weeks.

Transparent coatings: Both sides of the Aluzinc[®] alloy coated steel are coated with a transparent layer that provides protection and a uniform substrate for further coatings. This transparent coating allows identification of the aluminium-zinc substrate to be made by distributors and customers.

Colours

Moss Green

Brown



Ironbark

Red





Shingle Red Brown



Scarlet



Coal Black

Textured surface

Stone chip granules are applied to provide an attractive textured finish which at the same time enhance resistance to UV radiation. Granules are ceramic coated with lightfast heat resistant pigments.